

Equipped with a GUI menu screen for clear visibility and a joystick for intuitive control.

Compact Remote Camera Controller with PoE\*1 support for single cable connection.




### Equipped with a 3.5-type LCD screen

The AW-RP60 is equipped with a 3.5-type LCD screen to deliver a GUI menu where the information you need is provided at a glance for intuitive and quick camera control.



### New Joystick with enhanced operability

The new joystick supports smooth pan and tilt operations and ensures accurate capture of your target image. The grip of joystick is approximately 1.5 times larger than previous model AW-RP50, realizing more stable operation.



### Flexible customization features


The controller is equipped with four user assignable buttons, to which up to eight functions\*2 of your choice can be assigned. Each preset name can also be customized with a PC tool. These flexible features of the controller make it perfect for use in a wide range of environments, from lectures and corporate seminars to live streaming and broadcasting at amusement facilities.

### PoE\*1 support/Advanced camera adjustment


PoE\*1 support enables power supply and camera control to be delivered via a single ethernet cable. In addition to camera control operation, gamma, white balance and other color adjustment functions can be performed, making advanced camera adjustments possible.

\*1: PoE is the abbreviation for Power over Ethernet. \*2: Enable user button 5 through 8 by pressing the shift button.

<Rear View>



<Dimensions>



<Specifications>

Power Requirements	12 V DC (10.8 V to 13.2 V)	
PoE*	IEEE802.3af standard: 42 V to 57 V DC	
Current Consumption	0.9 A (XLR connector input), 0.3 A (PoE power supply)	
Mass	1.5 kg (3.31 lbs)	
Dimensions	W 210 mm x H 92 mm x D 177 mm (8-9/32 inches x 3-5/8 inches x 6-31/32 inches) (excluding protrusions)	
Display	3.5-type liquid crystal (QHD 960 x 540)	
Connection Specifications	No. of Connectable Cameras	200 (IP), 5 (RS422)
	Remote Camera Selection	5 (6 to 200 controlled from the LCD)
	No. of Camera Groups	20 (10 units/group)
	No. of Memory Presets	100

\*PoE is the abbreviation for Power over Ethernet.

- Power supply not included. An AC adaptor or PoE HUB is required.
- Specifications are subject to change without prior notice.

■ Optional Products



AC Adaptor  
AW-PS551

•See the Panasonic website for information on compatible third-party equipment  
<<https://pro-av.panasonic.net/en/support/>>.



Panasonic Connect Co., Ltd.  
2-15 Matsuba-cho, Kadoma, Osaka 571-8503 Japan



Factories of Panasonic Connect Co., Ltd. have received ISO14001:2015-the Environmental Management System certification. (Except for 3rd party's peripherals.)



For more information, please visit Panasonic web site  
<https://pro-av.panasonic.net/en/qr/>



Broadcast and Professional AV Website



Contact Information



Facebook



Mobile App